

WSW 080÷560Application: **2-Standard**Modality: **C-Chiller**Noise version: **N-Standard**Power Supply: **A-400/3/50**

SIZE	SEPR
080	8,10
090	8,22
110	7,92
125	8,02
140	7,93
160	8,31
180	8,55
220	8,16
250	8,24
265	7,99
280	8,00
320	8,11
360	8,32
420	8,24
480	8,14
560	8,19

Seasonal SEPR performance for process chillers high temperature Regulation (UE) 2016

Capacity control: **Variable**Refrigerant: **R-134a**GWP of the refrigerant: **1430 kg CO₂ eq**Outdoor side heat exchanger of the chiller: **water**Indoor side heat exchanger of the chiller: **water**

WSW 080÷560Application: **2-Standard**Modality: **C-Chiller**Noise version: **N-Standard**Power Supply: **B-460/3/60**

SIZE	SEPR
080	8,10
090	8,09
110	7,93
125	7,92
140	8,18
160	8,29
180	8,39
220	8,19
250	8,52
265	8,20
280	8,21
320	8,08
360	8,16
420	8,10
480	8,40
560	8,41

Seasonal SEPR performance for process chillers high temperature Regulation (UE) 2016

Capacity control: **Variable**Refrigerant: **R-134a**GWP of the refrigerant: **1430 kg CO2 eq**Outdoor side heat exchanger of the chiller: **water**Indoor side heat exchanger of the chiller: **water**